

SUORITUSTASOILMOITUS


DoP Nro: **MKT-1.4-101_fi**

- ◊ Tuotetyypin yksilöllinen tunniste: **Kiila-ankkuri BZ3 dynamic**
- ◊ Aiottu käyttötarkoitus (aiotut käyttötarkoitukset): Jälkiasennetut kiinnikkeet betoniin väsymiseen liittyvässä syklisessä kuormituksessa, ks. Liite / Annex B
- ◊ Valmistaja: **MKT Metall-Kunststoff-Technik GmbH & Co.KG**
Auf dem Immel 2
67685 Weilerbach
- ◊ Suoritustason pysyvyyden arvioinnissa ja varmentamisessa käytetty järjestelmä/käytetyt järjestelmät: 1
- ◊ Eurooppalainen arvointiasiakirja: **EAD 330250-00-0601**
Eurooppalainen tekninen arvointi: **ETA-20/0117, 20.02.2023**
Teknisestä arvioinnista vastaava laitos: DIBt, Berlin
Ilmoitettu laitos/ilmoitetut laitokset: NB 2873 – Technische Universität Darmstadt
- ◊ Ilmoitettu suoritustaso/ilmoitetut suoritustasot:

Olellaiset ominaisuudet	Suoritustaso
Mekaaninen lujuus ja vakuus (BWR 1)	
Ominaisresistanssit vetolujuudessa (staattiset ja lähes staattiset vaikutukset)	Liite/Annex B3, C2, C3
Ominaisresistanssit poikittaisessa rasituksessa (staattiset ja lähes staattiset vaikutukset)	Liite/Annex C4
Vuorossa	Liite/Annex C8, C9
Ominaisvastus ja siirtymät seismiselle suorituskykyluokalle C1 + C2	Liite/Annex C5
Kierrätettävyys	Liite/Annex B1
Ominainen väsymiskestävyys syklisessä vetolujuudessa	Liite/Annex C1
Ominainen väsymiskestävyys syklissä poikittaiskuormituksissa	
Ominainen väsymiskestävyys yhdistetyissä syklisissä vetolujuuksissa ja poikittaisissa kuormituksissa	
Kuormituskerroin syklisissä vetovastuksissa ja poikittaisissa kuormissa	
Paloturvallisuus (BWR 2)	
Palokäyttäytyminen	Luokka A1
Palonkestävyys	Liite/Annex C6, C7

Edellä yksilöidyn tuotteen suoritustaso on ilmoitettujen suoritustasojen joukon mukainen. Tämä suoritustasoilmoitus on asetuksen (EU) N:o 305/2011 mukaisesti annettu edellä ilmoitetun valmistajan yksinomaisella vastuulla.

Valmistajan puolesta allekirjoittanut:



Stefan Weustenhagen

(Toimitusjohtaja)

Weilerbach, 20.02.2023



Dipl.-Ing. Detlef Bigalke

(Tuotekehityksen johtaja)



Tämän suoritusilmoituksen alkuperäinen teksti on kirjoitettu saksaksi. Jos käänökset poikkeavat toisistaan, saksankielinen versio on pätevä.

Specifications of intended use

Anchorage subject to:

- Fatigue cyclic loading
- Static and quasi-static action, fire exposure and seismic performance according to ETA-19/0619

Base materials:

- Cracked or uncracked concrete
- Compacted, reinforced or unreinforced normal weight concrete without fibres according to EN 206:2013+A1:2016
- Strength classes C20/25 to C50/60 according to EN 206:2013+A1:2016

Use conditions (Environmental conditions):

- Structures subject to dry internal conditions
- For all other conditions according to EN 1993-1-2006+A1:2015-10, corresponding to corrosion resistance classes CRC according to Annex A2, Table A2

Design:

- Anchorages are designed under the responsibility of an engineer experienced in anchorages and concrete work.
- Verifiable calculation notes and drawings are prepared taking account of the loads to be anchored. The position of the fastener is indicated on the design drawings (e.g. position of the fastener relative to reinforcement or to supports, etc.).
- Design method EN 1992-4:2018, TR 055:2018 and TR 061:2020 (design method II)

Installation:

- Hole drilling by hammer drill bit or vacuum drill bit
- Use of the fastener only as supplied by the manufacturer without exchanging the components of the fastener

Wedge Anchor BZ3 dynamic


Intended use
Specifications of intended use

Annex B1

Table B1: Installation parameters

Anchor size			M10	M12	M16	
Nominal drill hole diameter	$d_0 =$	[mm]	10	12	16	
Cutting diameter of drill bit	$d_{cut} \leq$	[mm]	10,45	12,5	16,5	
Effective anchorage depth ¹⁾	$h_{ef} \geq$	[mm]	60	70	85	
Depth of drill hole	$h_0 \geq$	[mm]	$h_{ef} + 9$	$h_{ef} + 10$	$h_{ef} + 14$	
	$h_1 \geq$	[mm]	$h_{ef} + 11$	$h_{ef} + 13$	$h_{ef} + 17$	
Diameter of clearance hole in the fixture	$d_f =$	[mm]	12	14	18	
Minimum fixture thickness	$t_{fix,min} =$	[mm]	5	6	8	
Installation torque	vz	$T_{inst} =$	[Nm]	40	60	110
	A4 / HCR	$T_{inst} =$	[Nm]	40	55	100
Overstand	$h_p \leq$	[mm]	$21,5 + t_{fix}$	$25,5 + t_{fix}$	$29,5 + t_{fix}$	
Length of fastener	L	[mm]	$h_{ef} + t_{fix} + 30,5$	$h_{ef} + t_{fix} + 35,5$	$h_{ef} + t_{fix} + 43$	
Hexagon nut	width across nut	[mm]	17	19	24	
Locknut	width across nut	[mm]	17	19	24	

¹⁾ End of thread must be above the concrete surface



Wedge Anchor BZ3 dynamic

Intended use
Installation parameters

Annex B2

Table B2: Minimum thickness of concrete member, minimum spacings, edge distances and required area

Anchor size	M10	M12	M16		
Minimum member thickness depending on h_{ef}	$h_{min} \geq [mm]$		$1,5 \cdot h_{ef}$		
Minimum edge distances and spacings					
Minimum edge distance for $s \geq$	$c_{min} [mm]$	45	55		
	$[mm]$	see Table B4			
Minimum spacings for $c \geq$	$s_{min} [mm]$	40	50		
	$[mm]$	see Table B4			
The following equation must be fulfilled for the calculation of the minimum spacing and edge distance during installation in connection with the anchorage depth and the member thickness:					
$A_{sp,rqd} \leq A_{sp,ef}$					
Required splitting area $A_{sp,rqd}$ and idealized splitting area $A_{sp,ef}$ acc. to Table B4.					

Table B3: Applicable concrete thickness h_{sp} and area A_{sp} to determine characteristic edge distance $c_{cr,sp}$

Anchor size	M10	M12	M16
Applicable concrete thickness			
Area to determine $c_{cr,sp}$	$h_{sp} [mm]$	$\min(h ; h_{ef} + 1,5 \cdot c \cdot \sqrt{2})$	
	vz	$A_{sp} [mm^2]$	$\frac{N_{Rk,sp}^0 + 2,040}{0,000693}$
	$A4$	$A_{sp} [mm^2]$	$\frac{N_{Rk,sp}^0 + 3,685}{0,000692}$
	HCR		$\frac{N_{Rk,sp}^0 + 3,738}{0,000875}$
			$\frac{N_{Rk,sp}^0 + 7,235}{0,000967}$
			$\frac{N_{Rk,sp}^0 + 7,847}{0,000951}$
			$\frac{N_{Rk,sp}^0 + 11,415}{0,000742}$

Wedge Anchor BZ3 dynamic

Intended use

Minimum spacings and edge distances

Required area and applicable concrete thickness

Annex B3

Table B4: Areas to determine spacings and edge distances for installation

Anchor size	M10	M12	M16		
The following equation must be fulfilled for the calculation of the minimum spacing and edge distance during installation in combination with variable anchorage depth and member thickness:					
$A_{sp,rqd} \leq A_{sp,ef}$					
Idealized splitting area $A_{sp,ef}$					
The spacings and edge distances shall be selected or rounded in steps of 5 mm.					
Member thickness: $h > h_{ef} + 1,5 \cdot c$					
Single anchor or anchor group with $s \geq 3 \cdot c$					
Effective anchorage depth	$h_{ef} < 1,5 \cdot c$	$A_{sp,ef} = (6 \cdot c) \cdot (1,5 \cdot c + h_{ef})$	[mm ²]		
Effective anchorage depth	$h_{ef} \geq 1,5 \cdot c$	$A_{sp,ef} = (6 \cdot c) \cdot (3 \cdot c)$	[mm ²]		
Anchor group ($s < 3 \cdot c$)					
Effective anchorage depth	$h_{ef} < 1,5 \cdot c$	$A_{sp,ef} = (3 \cdot c + s) \cdot (1,5 \cdot c + h_{ef})$	[mm ²]		
Effective anchorage depth	$h_{ef} \geq 1,5 \cdot c$	$A_{sp,ef} = (3 \cdot c + s) \cdot (3 \cdot c)$	[mm ²]		
Member thickness: $h \leq h_{ef} + 1,5 \cdot c$					
Single anchor or anchor group with $s \geq 3 \cdot c$					
Effective anchorage depth	$h_{ef} < 1,5 \cdot c$	$A_{sp,ef} = (6 \cdot c) \cdot h$	[mm ²]		
Effective anchorage depth	$h_{ef} \geq 1,5 \cdot c$	$A_{sp,ef} = (6 \cdot c) \cdot (h - h_{ef} + 1,5 \cdot c)$	[mm ²]		
Anchor group ($s < 3 \cdot c$)					
Effective anchorage depth	$h_{ef} < 1,5 \cdot c$	$A_{sp,ef} = (3 \cdot c + s) \cdot h$	[mm ²]		
Effective anchorage depth	$h_{ef} \geq 1,5 \cdot c$	$A_{sp,ef} = (3 \cdot c + s) \cdot (h - h_{ef} + 1,5 \cdot c)$	[mm ²]		
Required splitting area $A_{sp,rqd}$					
VZ	cracked concrete	$A_{sp,rqd}$ [mm ²]	23 700	31 500	42 300
	uncracked concrete	$A_{sp,rqd}$ [mm ²]	34 700	41 300	50 200
A4 HCR	cracked concrete	$A_{sp,rqd}$ [mm ²]	25 900	29 800	44 300
	uncracked concrete	$A_{sp,rqd}$ [mm ²]	35 700	35 300	54 800

Wedge Anchor BZ3 dynamic

Intended use

Areas to determine spacings and edge distances

Annex B4

Installation instructions

1		Drill hole perpendicular to concrete surface. If using a vacuum drill bit, proceed with step 3.
2		Blow out dust. Alternatively, vacuum clean down to the bottom of the hole.
3		Drive in fastener with filling washer until effective anchorage depth is reached.
4		Apply installation torque T_{inst} according to Table B1 by using torque wrench.
5		Screw on locknut until hand tight then tighten $\frac{1}{4}$ to $\frac{1}{2}$ turn.
6		Fill the annular gap between anchor and fixture with mortar (compressive strength $\geq 40 \text{ N/mm}^2$, e.g. MKT Injection System VMH, VMZ or VMU plus). Use enclosed reducing adapter. Observe the processing information of the mortar! The annular gap is completely filled, when excess mortar seeps out.

Wedge Anchor BZ3 dynamic

Intended use
Installation instructions

Annex B5

Table C1: Characteristic values of fatigue resistance

Anchor size		M10	M12	M16	
Tension load					
Steel failure					
Characteristic fatigue resistance					
VZ	4,6	6,2	9,7		
	A4	3,2	5,3	9,2	
	HCR	2,8	5,5	9,7	
Load-transfer factor for fastener groups		Ψ_{FN} [-]	0,5		
Pull-out					
Characteristic fatigue resistance		$\Delta N_{Rk,p,0,\infty}$ [kN]	0,5 $N_{Rk,p}$		
Concrete cone and splitting failure					
Characteristic fatigue resistance		$\Delta N_{Rk,c,0,\infty}$ [kN]	0,5 $N_{Rk,c}$		
		$\Delta N_{Rk,sp,0,\infty}$ [kN]	0,5 $N_{Rk,sp}$		
Effective anchorage depth		h_{ef} [mm]	60	70	85
Shear load					
Steel failure without lever arm					
Characteristic fatigue resistance	VZ	[kN]	2,5	4,0	7,5
	A4	[kN]	1,5	2,8	6,0
	HCR	[kN]	2,3	2,8	5,0
Load-transfer factor for fastener groups		Ψ_{FV} [-]	0,5		
Concrete pry-out failure					
Characteristic fatigue resistance		$\Delta V_{Rk,cp,0,\infty}$ [kN]	0,5 $V_{Rk,cp}$		
Concrete edge failure					
Characteristic fatigue resistance		$\Delta V_{Rk,c,0,\infty}$ [kN]	0,5 $V_{Rk,c}$		
Effective length of anchor		l_f [mm]	60	70	85
Diameter of anchor		d_{nom} [mm]	10	12	16
Tension and shear load					
Partial factor ¹⁾	$\gamma_{Ms,fat}$	[-]	1,35		
	$\gamma_{Mc,fat}$	[-]	1,5		
	$\gamma_{Msp,fat}$	[-]	1,5		
	$\gamma_{Mp,fat}$	[-]	1,5		
Exponents for combined loading	α_s	[-]	0,5	0,5	0,7
	α_c	[-]	1,5		

¹⁾ In absence of other national regulations

Wedge Anchor BZ3 dynamic

Performance

Characteristic values of fatigue resistance

Annex C1

Table C2: Characteristic values for **tension loads** under static and quasi-static action, **steel, zinc plated**

Anchor size			M10	M12	M16
Installation factor	γ_{inst}	[-]	1,0		
Steel failure					
Characteristic resistance	$N_{Rk,s}$	[kN]	30,4	44,9	79,3
Partial factor ¹⁾	γ_{Ms}	[-]	1,5		
Pull-out					
Characteristic resistance in cracked concrete C20/25	$N_{Rk,p,cr}$	[kN]	15	22	30
Increasing factor $N_{Rk,p,cr} = \psi_c \cdot N_{Rk,p,cr}$ (C20/25)	ψ_c	[-]	$\left(\frac{f_{ck}}{20}\right)^{0,265}$	$\left(\frac{f_{ck}}{20}\right)^{0,5}$	$\left(\frac{f_{ck}}{20}\right)^{0,339}$
Characteristic resistance in uncracked concrete C20/25	$N_{Rk,p,ucr}$	[kN]	24	30	50
Increasing factor $N_{Rk,p,ucr} = \psi_c \cdot N_{Rk,p,ucr}$ (C20/25)	ψ_c	[-]	$\left(\frac{f_{ck}}{20}\right)^{0,448}$	$\left(\frac{f_{ck}}{20}\right)^{0,5}$	$\left(\frac{f_{ck}}{20}\right)^{0,203}$
Splitting					
Characteristic resistance	$N^0_{Rk,sp}$	[kN]	$\min(N_{Rk,p}; N^0_{Rk,c})$ ³⁾		
Characteristic edge distance ²⁾	$c_{cr,sp}$	[mm]	$\frac{A_{sp} + 0,8 \cdot (h_{sp} - h_{ef})^2}{(3,41 \cdot h_{sp} - 0,59 \cdot h_{ef})}$		
Characteristic spacing	$s_{cr,sp}$	[mm]	$2 \cdot c_{cr,sp}$		
Concrete cone failure					
Effective anchorage depth	h_{ef}	[mm]	60	70	85
Characteristic edge distance	$c_{cr,N}$	[mm]	$1,5 \cdot h_{ef}$		
Characteristic spacing	$s_{cr,N}$	[mm]	$2 \cdot c_{cr,N}$		
Factor	cracked concrete	$k_{cr,N}$	7,7		
	uncracked concrete	$k_{ucr,N}$	11,0		

¹⁾ In absence of other national regulations

²⁾ Applicable concrete thickness h_{sp} and area A_{sp} to determine characteristic edge distance $c_{cr,sp}$ according to Table B3

³⁾ $N^0_{Rk,c}$ according to EN 1992-4:2018

Wedge Anchor BZ3 dynamic

Performance

Characteristic values for **tension loads, steel, zinc plated**

Annex C2

Table C3: Characteristic values for **tension loads** under static or quasi-static action,
A4 and HCR

Anchor size			M10	M12	M16
Installation factor	γ_{inst}	[·]	1,0		
Steel failure					
Characteristic resistance	$N_{Rk,s}$	[kN]	30,4	44,9	74,6
Partial factor ¹⁾	γ_{Ms}	[·]	1,5		
Pull-out					
Characteristic resistance in cracked concrete C20/25	$N_{Rk,p,cr}$	[kN]	17	22	35
Increasing factor $N_{Rk,p,cr} = \psi_c \cdot N_{Rk,p,cr}$ (C20/25)	ψ_c	[·]	$\left(\frac{f_{ck}}{20}\right)^{0,5}$	$\left(\frac{f_{ck}}{20}\right)^{0,435}$	$\left(\frac{f_{ck}}{20}\right)^{0,350}$
Characteristic resistance in uncracked concrete C20/25	$N_{Rk,p,ucr}$	[kN]	25	42	50
Increasing factor $N_{Rk,p,ucr} = \psi_c \cdot N_{Rk,p,ucr}$ (C20/25)	ψ_c	[·]	$\left(\frac{f_{ck}}{20}\right)^{0,364}$	$\left(\frac{f_{ck}}{20}\right)^{0,213}$	$\left(\frac{f_{ck}}{20}\right)^{0,196}$
Splitting					
Characteristic resistance	$N_{Rk,sp}^0$	[kN]	$\min(N_{Rk,p}; N_{Rk,c}^0)$		
Characteristic edge distance ²⁾	$c_{cr,sp}$	[mm]	$\frac{A_{sp} + 0,8 \cdot (h_{sp} - h_{ef})^2}{(3,41 \cdot h_{sp} - 0,59 \cdot h_{ef})}$		
Characteristic spacing	$s_{cr,sp}$	[mm]	$2 \cdot c_{cr,sp}$		
Concrete cone failure					
Effective anchorage depth	h_{ef}	[mm]	60	70	85
Characteristic edge distance	$c_{cr,N}$	[mm]	$1,5 \cdot h_{ef}$		
Characteristic spacing	$s_{cr,N}$	[mm]	$2 \cdot c_{cr,N}$		
Factor	cracked concrete	$k_{cr,N}$	[·]	7,7	
	uncracked concrete	$k_{ucr,N}$	[·]	11,0	

¹⁾ In absence of other national regulations

²⁾ Applicable concrete thickness h_{sp} and area A_{sp} according to Table B3 to determine characteristic edge distance $c_{cr,sp}$

³⁾ $N_{Rk,c}^0$ according to EN 1992-4:2018

Wedge Anchor BZ3 dynamic

Performance
Characteristic values for **tension loads**, **A4** and **HCR**

Annex C3

Table C4: Characteristic values for **shear loads** under static and quasi-static action

Anchor size			M10	M12	M16
Installation factor	γ_{inst}	[-]	1,0		
Steel failure without lever arm					
Characteristic resistance	vz A4 / HCR	$V^0_{Rk,s}$ $V^0_{Rk,s}$	[kN] [kN]	26,8 27,8	38,3 39,8
Partial factor ¹⁾		γ_{Ms}	[-]	1,25	
Ductility factor		k_7	[-]	1,0	
Steel failure with lever arm					
Characteristic bending resistance	vz A4 / HCR	$M^0_{Rk,s}$ $M^0_{Rk,s}$	[Nm] [Nm]	60 55	105 99
Partial factor ¹⁾		γ_{Ms}	[-]	1,25	
Concrete pry-out failure					
Pry-out factor	vz A4 / HCR	k_8 k_8	[-] [-]	3,1 2,8	3,0 3,3
Concrete edge failure					
Effective length of fastener in shear loading		l_f	[mm]	h_{ef}	
Outside diameter of fastener		d_{nom}	[mm]	10	12
1) In absence of other national regulations					

Wedge Anchor BZ3 dynamic

Performance

Characteristic values for **shear loads**

Annex C4

Table C5: Characteristic values for **seismic loading**, performance category **C1**

Anchor size			M10	M12	M16
Effective anchorage depth	$h_{\text{ef}} \geq$	[mm]	60	70	85
Tension load					
Installation factor	γ_{inst}	[-]	1,0		
Steel failure					
Characteristic resistance	vz A4 / HCR	$N_{Rk,s,C1}$ $N_{Rk,s,C1}$	[kN] [kN]	30,4 30,4	44,9 44,9
Pull-out					
Characteristic resistance	vz A4 / HCR	$V_{Rk,s,C1}$ $V_{Rk,s,C1}$	[kN] [kN]	15,0 17,0	22,0 22,0
Shear load					
Steel failure without lever arm					
Characteristic resistance	vz A4 / HCR	$V_{Rk,s,C1}$ $V_{Rk,s,C1}$	[kN] [kN]	24,4 22,2	33,8 33,2
Factor for anchorages without annular gap	α_{gap}	[-]	1,0		

Table C6: Characteristic values for **seismic loading**, performance category **C2**

Anchor size			M10	M12	M16
Effective anchorage depth	$h_{\text{ef}} \geq$	[mm]	60	70	85
Tension load					
Installation factor	γ_{inst}	[-]	1,0		
Steel failure					
Characteristic resistance	vz A4 / HCR	$N_{Rk,s,C2}$ $N_{Rk,s,C2}$	[kN] [kN]	30,4 30,4	44,9 44,9
Pull-out					
Characteristic resistance	vz A4 / HCR	$N_{Rk,p,C2}$ $N_{Rk,p,C2}$	[kN] [kN]	12,5 7,7	19,0 13,8
Shear load					
Steel failure without lever arm					
Characteristic resistance	vz A4 / HCR	$V_{Rk,s,C2}$ $V_{Rk,s,C2}$	[kN] [kN]	19,0 15,9	28,0 25,6
Factor for anchorages without annular gap	α_{gap}	[-]	1,0		

Wedge Anchor BZ3 dynamic

Performance
Characteristic resistance for **seismic loading**

Annex C5

Table C7: Characteristic values for tension and shear load under fire exposure, steel, zinc plated

Anchor size		M10	M12	M16	
Tension load					
Steel failure					
Characteristic resistance	R30	N _{Rk,s,fi} [kN]	2,6	4,6	7,7
	R60		1,9	3,3	5,6
	R90		1,3	2,1	3,5
	R120		1,0	1,5	2,5
Shear load					
Steel failure without lever arm					
Characteristic resistance	R30	V _{Rk,s,fi} [kN]	7,5	12,3	20,7
	R60		5,1	8,5	14,2
	R90		2,7	4,6	7,7
	R120		1,6	2,7	4,5
Steel failure with lever arm					
Characteristic resistance	R30	M ⁰ _{Rk,s,fi} [Nm]	9,6	19,1	43,8
	R60		6,6	13,1	30,1
	R90		3,5	7,2	16,4
	R120		2,0	4,2	9,6

N_{Rk,p,fi} and N_{Rk,c,fi} according to EN 1992-4:2018

Wedge Anchor BZ3 dynamic

Performance

Characteristic values under **fire exposure, steel, zinc plated**

Annex C6

Table C8: Characteristic values for tension and shear load under fire exposure, A4 and HCR

Anchor size		M10	M12	M16	
Tension load					
Steel failure					
Characteristic resistance	R30	N _{Rk,s,fi} [kN]	6,9	11,0	18,1
	R60		5,0	8,0	13,1
	R90		3,1	4,9	8,1
	R120		2,1	3,4	5,6
Shear load					
Steel failure without lever arm					
Characteristic resistance	R30	V _{Rk,s,fi} [kN]	17,6	32,0	52,6
	R60		12,6	22,6	37,1
	R90		7,5	13,1	21,5
	R120		5,0	8,4	13,8
Steel failure with lever arm					
Characteristic resistance	R30	M ⁰ _{Rk,s,fi} [Nm]	22,7	49,8	111,5
	R60		16,2	35,1	78,6
	R90		9,7	20,4	45,6
	R120		6,5	13,0	29,2

N_{Rk,p,fi} and N_{Rk,c,fi} according to EN 1992-4:2018

Wedge Anchor BZ3 dynamic

Performance

Characteristic values under **fire exposure, A4 and HCR**

Annex C7

Table C9: Displacements under tension load, steel, zinc plated

Anchor size	M10	M12	M16	
Displacements under static or quasi-static action				
$\delta_{N0} = \delta_{N0\text{-factor}} * N$ N: acting tension load				
$\delta_{N\infty} = \delta_{N\infty\text{-factor}} * N$				
Cracked concrete				
Factor for displacement	$\delta_{N0\text{-factor}}$ [mm/kN]	0,05	0,04	0,03
	$\delta_{N\infty\text{-factor}}$ [mm/kN]	0,20	0,15	0,11
Uncracked concrete				
Factor for displacement	$\delta_{N0\text{-factor}}$ [mm/kN]	0,01	0,004	0,005
	$\delta_{N\infty\text{-factor}}$ [mm/kN]	0,03	0,03	0,03
Displacement under seismic action C2				
Displacements for DLS	$\delta_{N,C2(DLS)}$ [mm]	4,7	4,2	4,5
Displacements for ULS	$\delta_{N,C2(ULS)}$ [mm]	16,1	12,9	12,8

Table C10: Displacements under tension load, A4 and HCR

Anchor size	M10	M12	M16	
Displacements under static or quasi-static action				
$\delta_{N0} = \delta_{N0\text{-factor}} * N$ N: acting tension load				
$\delta_{N\infty} = \delta_{N\infty\text{-factor}} * N$				
Cracked concrete				
Factor for displacement	$\delta_{N0\text{-factor}}$ [mm/kN]	0,06	0,05	0,02
	$\delta_{N\infty\text{-factor}}$ [mm/kN]	0,17	0,16	0,08
Uncracked concrete				
Factor for displacement	$\delta_{N0\text{-factor}}$ [mm/kN]	0,00	0,001	0,00
	$\delta_{N\infty\text{-factor}}$ [mm/kN]	0,05	0,05	0,05
Displacement under seismic action C2				
Displacements for DLS	$\delta_{N,C2(DLS)}$ [mm]	4,1	5,7	5,1
Displacements for ULS	$\delta_{N,C2(ULS)}$ [mm]	16,8	18,0	13,9

Wedge Anchor BZ3 dynamic**Performance**

Displacements under tension load

Annex C8

Table C11: Displacements under **shear load, steel, zinc plated**

Anchor size	M10	M12	M16	
Displacements under static or quasi-static action				
$\delta_{V0} = \delta_{V0\text{-factor}} * V$ V: acting shear load				
Factor for displacement	$\delta_{V0\text{-factor}}$ [mm/kN]	0,09	0,09	0,07
	$\delta_{V\infty\text{-factor}}$ [mm/kN]	0,13	0,14	0,11
Displacement under seismic action C2				
Displacements for DLS	$\delta_{V,C2(\text{DLS})}$ [mm]	3,1	3,7	3,8
Displacements for ULS	$\delta_{V,C2(\text{ULS})}$ [mm]	5,5	9,9	9,6

Table C12: Displacements under **shear load, A4 and HCR**

Anchor size	M10	M12	M16	
Displacements under static or quasi-static action				
$\delta_{V0} = \delta_{V0\text{-factor}} * V$ V: acting shear load				
Factor for displacement	$\delta_{V0\text{-factor}}$ [mm/kN]	0,14	0,12	0,09
	$\delta_{V\infty\text{-factor}}$ [mm/kN]	0,20	0,17	0,14
Displacement under seismic action C2				
Displacements for DLS	$\delta_{V,C2(\text{DLS})}$ [mm]	3,5	4,2	4,4
Displacements for ULS	$\delta_{V,C2(\text{ULS})}$ [mm]	8,4	11,8	11,1

Wedge Anchor BZ3 dynamic**Performance**

Displacements under shear load

Annex C9